

xroll

3 YEARS WARRANTY



EN

Ceiling light fittings equipped with SMD LEDs. Housing of die-cast aluminum, electrostatically painted. Diffusers of opal polystyrene (RX02) and polycarbonate (RX03). Constant current LED driver included. Block of terminals 2P+N (10A/250V/2,5mm²).

Range of applications

General interior lighting.

RO

Plafoniere echipate cu LED-uri SMD. Carcasa din aluminiu turnat, vopsită în câmp electrostatic. Dispersoare opale din polistiren (RX02) și policarbonat (RX03). Alimentator LED în curent constant inclus. Clemă de conexiuni 2P+N (10A/250V/2,5mm²).

Aplicații

Iluminatul general de interior.

IT

Apparecchi d'illuminazione con montaggio a soffitto, equipaggiati con LED SMD. Corpo in alluminio pressofuso, vernicio a polveri. Diffusori opalini in polistirene (RX02) e policarbonato (RX03).

Alimentatore LED in corrente costante incluso.

Morsettiere 2P+N (10A/250V/2,5mm²).

Campi di applicazione



Illuminazione generale d'interni.

RX02

FINISHING AVAILABLE

MWH

IP44





Code	Finishing	LED type	Power	Input voltage	Driver	LED Flux	System Flux	CCT	CRI	Optics	Weight
RX02WW MWH	MWH	SMD 2835 SAN'AN	9W	220-240V AC	Included	1080 lm	678 lm	3000K	80	120°	0.29 kg
RX02NW MWH	MWH	SMD 2835 SAN'AN	9W	220-240V AC	Included	1140 lm	719 lm	4000K	80	120°	0.29 kg

RX03

FINISHING AVAILABLE

MWH

IP40



Code	Finishing	LED type	Power	Input voltage	Driver	LED Flux	System Flux	CCT	CRI	Optics	Weight
RX03WW MWH	MWH	SMD 2835 SAN'AN	18W	220-240V AC	Included	2040 lm	1458 lm	3000K	80	120°	0.50 kg
RX03NW MWH	MWH	SMD 2835 SAN'AN	18W	220-240V AC	Included	2230 lm	1531 lm	4000K	80	120°	0.50 kg