

# MINIMA SQUARE LED IP65 FIRE-RATED 5771

SKU 1249014

astro



## PRODUCT SPECIFICATION

### GENERAL

<b>FINISH:</b>	White	<b>CABLE LENGTH:</b>	1000 (mm)
<b>MAIN MATERIAL:</b>	Metal - Mild Steel	<b>GROSS WEIGHT:</b>	0.584 (Kg)
<b>DIMENSIONS:</b>	H: 95mm W: 95mm D: 92mm	<b>CLASS:</b>	CE (Class III)
<b>INSTALLATION ORIENTATION:</b>	Ceiling Mount	<b>IP RATING:</b>	IP65
<b>CUT OUT HOLE:</b>	L: 86mm W: 86mm	<b>BATHROOM ZONE:</b>	Zone 1, 2, 3
<b>RECESS DEPTH:</b>	100 (mm)	<b>VOLTAGE:</b>	Mains 230 (V)
<b>FIRE RATING:</b>	90min	<b>PRODUCT F MARK:</b>	Suitable for mounting on flammable materials.

### LAMP


<b>LIGHT SOURCE:</b>	COB LED	<b>MACADAM ELIPSE:</b>	3-Step
<b>MAXIMUM WATTAGE:</b>	6.5W	<b>UGR:</b>	To Be Advised
<b>MAXIMUM LAMP LENGTH:</b>	Not Applicable	<b>BEAM ANGLE:</b>	40 (Degrees)
<b>LAMP INCLUDED?</b>	Yes (Integral)	<b>TILT ADJUSTMENT ANGLE:</b>	Not Applicable
<b>LUMINOUS FLUX:</b>	538.96 (lm)	<b>ROTATION ADJUSTMENT ANGLE:</b>	Not Applicable
<b>COLOUR TEMP:</b>	2700 (K)	<b>AVERAGE LIFESPAN:</b>	40,000 (Hrs)
<b>CRI:</b>	82	<b>L70:</b>	To Be Advised
<b>R9:</b>	10.0		

### ELECTRICAL

<b>SWITCHED:</b>	No	<b>SUPPLY FREQUENCY:</b>	50 (Hz)
<b>DIMMABLE:</b>	Yes	<b>DRIVER/BALLAST VOLTAGE:</b>	220-240 (V)
<b>DIMMING METHOD:</b>	Phase - Leading & Trailing Edge	<b>DRIVER AVERAGE LIFESPAN:</b>	40,000 (Hrs)
<b>DRIVER OUTPUT CURRENT:</b>	180 (mA)	<b>EFFICACY:</b>	68.22 (lm/w)
<b>DRIVER OUTPUT VOLTAGE:</b>	Not Applicable	<b>DRIVER/BALLAST INCLUDED?</b>	Yes

## ADDITIONAL INFORMATION

CE



BOX QUANTITY x 20

PRODUCT ELEVATIONS

---

