

ASCOLI FLOOR 4582

SKU 1286018

astro



PRODUCT SPECIFICATION

GENERAL

| | | | |
|----------------------------------|---|------------------------|----------------|
| FINISH: | Matt White | CABLE LENGTH: | 3000 (mm) |
| MAIN MATERIAL: | Metal - Mild Steel | GROSS WEIGHT: | 6.68 (Kg) |
| DIMENSIONS: | H: 1225mm W: 200mm D: 285mm DIA: 200mm | CLASS: | CE (Class II) |
| INSTALLATION ORIENTATION: | Not Applicable | IP RATING: | IP20 |
| CUT OUT HOLE: | Not Applicable | BATHROOM ZONE: | Zone 3 |
| RECESS DEPTH: | Not Applicable | VOLTAGE: | Mains 230 (V) |
| FIRE RATING: | Not Applicable | PRODUCT F MARK: | Not Applicable |

LAMP


| | | | |
|-----------------------------|----------------|-----------------------------------|----------------|
| LIGHT SOURCE: | LED GU10 | MACADAM ELIPSE: | Not Applicable |
| MAXIMUM WATTAGE: | 6W | UGR: | Not Applicable |
| MAXIMUM LAMP LENGTH: | To Be Advised | BEAM ANGLE: | Not Applicable |
| LAMP INCLUDED? | No | TILT ADJUSTMENT ANGLE: | 90 (Degrees) |
| LUMINOUS FLUX: | Lamp Dependent | ROTATION ADJUSTMENT ANGLE: | 330 (Degrees) |
| COLOUR TEMP: | Lamp Dependent | AVERAGE LIFESPAN: | Lamp Dependent |
| CRI: | Lamp Dependent | L70: | Not Applicable |
| R9: | Lamp Dependent | | |

ELECTRICAL

| | | | |
|-------------------------------|----------------|-----------------------------------|----------------|
| SWITCHED: | Yes | SUPPLY FREQUENCY: | Not Applicable |
| DIMMABLE: | No | DRIVER / BALLAST VOLTAGE: | Not Applicable |
| DIMMING METHOD: | Not Applicable | DRIVER AVERAGE LIFESPAN: | Not Applicable |
| DRIVER OUTPUT CURRENT: | Not Applicable | EFFICACY: | Not Applicable |
| DRIVER OUTPUT VOLTAGE: | Not Applicable | DRIVER / BALLAST INCLUDED? | No |

ADDITIONAL INFORMATION

CE



BOX QUANTITY x1

PRODUCT ELEVATIONS

