



# FRIDA

78

Exposed downlights



BK \*

**FRIDA 7W 3000K / 4000K**

LED integrated

voltage: 230V

LED 7W 500lm 3000K

**LED**

IP54



LED 7W 550lm 4000K

technical

installation place  inlet opening 7-8cm

specification


beam angle: 24°

COLOUR / NEW INDEX NO.

- 3000K WHITE (WH) . . . . . **AZ4525**
- 3000K BLACK (BK) . . . . . **AZ4523**
- 4000K WHITE (WH) . . . . . **AZ4526**
- 4000K BLACK (BK) . . . . . **AZ4524**



Ø 8,5



WH \*

**FRIDA 12W 3000K / 4000K**

LED integrated

voltage: 230V

LED 12W 1100lm 3000K

**LED**

IP54



LED 12W 1100lm 4000K

technical

installation place  inlet opening 7-8cm

specification

beam angle: 24°

COLOUR / NEW INDEX NO.

- 3000K WHITE (WH) . . . . . **AZ4529**
- 3000K BLACK (BK) . . . . . **AZ4527**
- 4000K WHITE (WH) . . . . . **AZ4530**
- 4000K BLACK (BK) . . . . . **AZ4528**



Ø 10



BK

BK

WH

WH

\* - EXPLANATION SHORTCUT PAGE 2 (E)

# FRIDA

Exposed downlights

79

