


One new


Source	LED SMD	LED life	30.000 h
Power	2W / 3W	Insulation class	II
Driver included	On/Off	IP	20
Drivers available	No	Material	Aluminum
CCT	3000 K	Warranty	5 years
CRI	≥95		



⌀ 17 mm
0,050 Kg/0,0001 m³

LED SMD Driver ON/OFF included*


Power	Beam	Lumen	CCT	Finish	Code	€
2W	25°	130 lm	3000 K	White	274768	28 new



⌀ 25 mm
0,070 Kg/0,0001 m³

LED SMD Driver ON/OFF included*

Power	Beam	Lumen	CCT	Finish	Code	€
2W	30°	130 lm	3000 K	White	274775	32 new




⌀ 35 mm
0,100 Kg/0,0003 m³

LED SMD Driver ON/OFF included*

Power	Beam	Lumen	CCT	Finish	Code	€
3W	25°	270 lm	3000 K	White	274782	36 new



Light beam: SPOT




m	lx	øm
1	372	0,40
2	93	0,81
3	41	1,20
4	23	1,60
5	15	2,00



CRI≥95 2W 25° 651m 3000K



Light beam: SPOT




m	lx	øm
1	307	0,53
2	77	1,10
3	34	1,60
4	19	2,10
5	12	2,70



CRI≥95 2W 30° 701m 3000K



Light beam: SPOT



m	lx	øm
1	866	0,40
2	216	0,80
3	96	1,20
4	54	1,60
5	35	2,00



CRI≥95 3W 25° 651m 3000K

* Measure L 38,3 x H 16,5 x W 19,3 mm