

Steel



General info


Technical - Linear system

Indoor suspended or ceiling mounted linear fitting with multiple integrated LED sources and direct/indirect light emission

| | |
|---------------------|-------------------------|
| Ean | 8021696267135 |
| Item | STEEL WIDE BK 4000K |
| Installation | Suspension / Ceiling |
| Guarantee | 5 years |
| Gross weight | 2.47 kg |
| Volume | 0.017817 m ³ |

Technical info

| | |
|------------------------------|--|
| Net weight | 1.99 kg |
| Insulation class | I |
| Protection index | IP20 |
| Operating temperature | 0° ~ +40 °C |
| Dimmer | Non-dimmable, On-Off |
| Power output | 220-240 V AC 50/60 Hz |
| Power supply | In-built, included YES (by qualified operators only), electronic, osram |



Source info

| | |
|-------------------------------|-----------------------------------|
| Integrated source | Integrated LED module |
| Replaceable source | YES (by qualified operators only) |
| Power | 36W |
| Emission | Direct + Indirect |
| Max consumption | max 36 W |
| Features LED | LED SMD SAMSUNG |
| CCT | 4000 K |
| Duration LED (t. 25°C) | 50000 h |
| CRI | > 90 |
| SDCM | 3 |
| Light beam | 70+110° |
| UGR Maximum | < 19 |
| Light beam flux | 3550 lm |
| Useful light flux | 2900 lm |
| Standby power | < 0.50 |