ideal lux.





rev. 24-08-2022

General info

Technical - Spotlights and Tracks

Indoor track mounted adjustable projector with integrated LED sources and direct light emission

Ean	8021696285368	
Item	FOX 08W CRI90 41° 3000K ON-OFF WH	
Installation	Eutrac 3-phase track (Ceiling, Wall)	
Guarantee	5 years	
Gross weight	0.35 kg	
Volume	0.001518 m³	

Technical info

Net weight	0.3 kg
Insulation class	I
Protection index	IP20
Operating temperature	0° ~ +40 °C
Dimmer	Non-dimmable, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included
	YES (by qualified operators only), electronic
Adjustability	vert. 0°-90° , orizz. 0°-355°
Accessories not included	Single connection on-off, Link on-off profile

70 100 100 100 100 52

Source info

Integrated sourceIntegrated LED moduleRepleaceable sourceYES (by qualified operators only)Power8WEmissionDirectMax consuptionmax 8,00 WFeatures LEDLED COB BRIDGELUXCCT3000 KDuration LED (t. 25°c)30000 hCRI> 90SDCM3Light beam flux750 ImUseful light flux700 ImStandby power< 0.50		
Power8WEmissionDirectMax consuptionmax 8,00 WFeatures LEDLED COB BRIDGELUXCCT3000 KDuration LED (t. 25°c)30000 hCRI> 90SDCM3Light beam41°Light beam flux750 ImUseful light flux700 Im	Integrated source	Integrated LED module
EmissionDirectMax consuptionmax 8,00 WFeatures LEDLED COB BRIDGELUXCCT3000 KDuration LED (t. 25°c)30000 hCRI> 90SDCM3Light beam41°Light beam flux750 lmUseful light flux700 lm	Repleaceable source	YES (by qualified operators only)
LinketonDirectMax consuptionmax 8,00 WFeatures LEDLED COB BRIDGELUXCCT3000 KDuration LED (t. 25°c)30000 hCRI> 90SDCM3Light beam41°Light beam flux750 lmUseful light flux700 lm	Power	8W
Features LEDLED COB BRIDGELUXCCT3000 KDuration LED (t. 25°c)30000 hCRI> 90SDCM3Light beam41°Light beam flux750 lmUseful light flux700 lm	Emission	Direct
CCT 3000 K Duration LED (t. 25°c) 30000 h CRI > 90 SDCM 3 Light beam flux 750 lm Useful light flux 700 lm	Max consuption	max 8,00 W
Duration LED (t. 25°c)30000 hCRI> 90SDCM3Light beam41°Light beam flux750 lmUseful light flux700 lm	Features LED	LED COB BRIDGELUX
CRI> 90SDCM3Light beam41°Light beam flux750 lmUseful light flux700 lm	ССТ	3000 K
SDCM 3 Light beam 41° Light beam flux 750 lm Useful light flux 700 lm	Duration LED (t. 25°c)	30000 h
Light beam41°Light beam flux750 lmUseful light flux700 lm	CRI	> 90
Light beam flux 750 lm Useful light flux 700 lm	SDCM	3
Useful light flux 700 lm	Light beam	41°
	Light beam flux	750 lm
Standby power < 0.50	Useful light flux	700 lm
	Standby power	< 0.50