ideal lux.





rev. 24-08-2022

General info

Technical - Spotlights and Tracks

Indoor track mounted adjustable projector with integrated LED sources and direct light emission

Ean	8021696285399
Item	FOX 25W CRI90 35° 3000K ON-OFF BK
Installation	Eutrac 3-phase track (Ceiling)
Guarantee	5 years
Gross weight	0.64 kg
Volume	0.002688 m ³

Technical info

Net weight	0.54 kg
Insulation class	I
Protection index	IP20
Operating temperature	0° ~ +40 °C
Dimmer	Non-dimmable, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included
	YES (by qualified operators only), electronic
Adjustability	vert. 0°-90° , orizz. 0°-355°
Accessories not included	Single connection on-off, Link on-off profile

Source info

Integrated source	Integrated LED module
Repleaceable source	YES (by qualified operators only)
Power	25W
Emission	Direct
Max consuption	max 25,00 W
Features LED	LED COB BRIDGELUX
ССТ	3000 K
Duration LED (t. 25°c)	30000 h
CRI	> 90
SDCM	3
Light beam	35°
Light beam flux	2350 lm
Useful light flux	2010 lm
Standby power	< 0.50