



# Aura



## General info

### Indoor - Ceiling lamps

|                     |                           |
|---------------------|---------------------------|
| <b>Ean</b>          | 8021696290812             |
| <b>Item</b>         | AURA PL SQUARE 3000K NERO |
| <b>Installation</b> | Ceiling lamps             |
| <b>Guarantee</b>    | 5 years                   |
| <b>Gross weight</b> | 0.5 kg                    |
| <b>Volume</b>       | 0.001829 m <sup>3</sup>   |

## Technical info

|                                |                                      |
|--------------------------------|--------------------------------------|
| <b>Net weight</b>              | 0.4 kg                               |
| <b>Insulation class</b>        | II                                   |
| <b>Protection index</b>        | IP20                                 |
| <b>Compliance</b>              | CE                                   |
| <b>Operating temperature</b>   | 0° ~ +40 °C                          |
| <b>Dimmer</b>                  | Non-dimmable, On-Off                 |
| <b>Power output</b>            | 220-240 V AC 50/60 Hz                |
| <b>Power supply</b>            | In-built, included<br>NO, electronic |
| <b>Recessed specifications</b> | 65...205 - h. ≥ 26                   |

## Source info

|                               |                       |
|-------------------------------|-----------------------|
| <b>Integrated source</b>      | Integrated LED module |
| <b>Replaceable source</b>     | No                    |
| <b>Power</b>                  | LED 20 W              |
| <b>Emission</b>               | Direct                |
| <b>Max consumption</b>        | max 20,00 W           |
| <b>Features LED</b>           | LED SMD               |
| <b>CCT</b>                    | 3000 K                |
| <b>Duration LED (t. 25°C)</b> | 30000 h               |
| <b>CRI</b>                    | > 80                  |
| <b>Light beam</b>             | 115°                  |
| <b>Light beam flux</b>        | 1950 lm               |
| <b>Useful light flux</b>      | 1690 lm               |
| <b>Photobiological risk</b>   | EXEMPT                |