

## General info


## Indoor - Wall lamps



|                     |                         |
|---------------------|-------------------------|
| <b>Ean</b>          | 8021696304502           |
| <b>Item</b>         | OZ AP DALI OTTONE       |
| <b>Installation</b> | Wall lamps              |
| <b>Guarantee</b>    | 5 years                 |
| <b>Gross weight</b> | 1.23 kg                 |
| <b>Volume</b>       | 0.008712 m <sup>3</sup> |

## Technical info

|                              |  |
|------------------------------|--|
| <b>Net weight</b>            | 0.8 kg   |
| <b>Insulation class</b>      | II   |
| <b>Protection index</b>      | IP20   |
| <b>Compliance</b>            | CE   |
| <b>Operating temperature</b> | 0° ~ +40 °C  |
| <b>Dimmer</b>                | Dimmable, DALI / Push  |
| <b>Power output</b>          | 220-240 V AC 50/60 Hz  |
| <b>Power supply</b>          | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |



## Source info

|                               |                       |
|-------------------------------|-----------------------|
| <b>Integrated source</b>      | Integrated LED module |
| <b>Replaceable source</b>     | No                    |
| <b>Power</b>                  | LED 28 W              |
| <b>Emission</b>               | Diffuse               |
| <b>Max consumption</b>        | max 28,00 W           |
| <b>Features LED</b>           | LED SMD               |
| <b>CCT</b>                    | 3000 K                |
| <b>Duration LED (t. 25°C)</b> | 30000 h               |
| <b>CRI</b>                    | > 80                  |
| <b>Light beam flux</b>        | 2500 lm               |
| <b>Useful light flux</b>      | 1060 lm               |
| <b>Photobiological risk</b>   | 1                     |
| <b>Standby power</b>          | < 0.50 W              |