

Kanlux

AREL LED

OPRAWA TYPU DOWNLIGHT ► DOWNLIGHT FITTING

NEW



AREL LED DO 20W



AREL LED DL 10W



IP 65/20

ultra SLIM panel

HIGH quality

Kanlux AREL LED to nowa rodzina downlightów, które nie posiadają ramki. Wysoka klasa szczelności IP65/20 oraz wyjątkowy, prosty, a zarazem zaskakujący design sprawia, że Kanlux AREL LED wpasuje się w każde wnętrze. Dzięki unikatowej konstrukcji, panel ma grubość zaledwie 9 mm – to najcieńszy panel dostępny na rynku.

Materiał obudowy: tworzywo sztuczne

Materiał klosza: PMMA


Kanlux AREL LED is a new family of downlights which do not have a frame. High tightness class IP65/20 and exceptional, simple, and at the same time surprising design make Kanlux AREL LED fit into each interior. Thanks to the unique structure, the panel is only 9 mm thick - it is the thinnest panel available on the market.

Enclosure material: plastic

Lampshade material: PMMA




AREL LED DO 6W-NW	29580	5905339295804	6	biały white	410	120	4000
AREL LED DO 6W-WW	29581	5905339295811	6	biały white	380	120	3000
AREL LED DL 6W-NW	29582	5905339295828	6	biały white	410	120	4000
AREL LED DL 6W-WW	29583	5905339295835	6	biały white	380	120	3000
AREL LED DO 10W-NW	29584	5905339295842	10	biały white	830	120	4000
AREL LED DO 10W-WW	29585	5905339295859	10	biały white	790	120	3000
AREL LED DL 10W-NW	29586	5905339295866	10	biały white	830	120	4000
AREL LED DL 10W-WW	29587	5905339295873	10	biały white	790	120	3000
AREL LED DO 14W-NW	29588	5905339295880	14	biały white	1150	120	4000
AREL LED DO 14W-WW	29589	5905339295897	14	biały white	1100	120	3000
AREL LED DL 14W-NW	29590	5905339295903	14	biały white	1150	120	4000
AREL LED DL 14W-WW	29591	5905339295910	14	biały white	1100	120	3000
AREL LED DO 20W-NW	29592	5905339295927	20	biały white	1710	120	4000
AREL LED DO 20W-WW	29593	5905339295934	20	biały white	1650	120	3000
AREL LED DL 20W-NW	29594	5905339295941	20	biały white	1710	120	4000
AREL LED DL 20W-WW	29595	5905339295958	20	biały white	1650	120	3000



AREL LED DL 6W


AREL LED DL 10W




AREL LED DL 14W

AREL LED DL 20W


[V] 220-240 AC	[Hz] 50/60	≥15000	30000	ellipse ≤ 6x MacAdam	Ra ≥80	SMD			IP 65/20
	5÷25		0,75-1,5	0,5m					




AREL LED DO 6W



AREL LED DO 10W



AREL LED DO 14W



AREL LED DO 20W