

# PRODUCT DATASHEET

## O SURFACE RD 13 W 3000 K IP54 GY

OUTDOOR SURFACE ROUND | Wall and ceiling luminaires with modern design in round shape



---

### AREAS OF APPLICATION

- Outdoor
- Building facades
- Gardens, balconies and other outdoor areas

---

### PRODUCT BENEFITS

- Energy-efficient thanks to LED technology
- 5 years guarantee
- Easy and quick installation
- Homogeneous light output

---

### PRODUCT FEATURES

- Bright and functional outdoor LED luminaires
- Type of protection: IP54
- Die-cast aluminum housing
- Available in two housing colors: white and dark gray
- Diffuser made of opal polycarbonate



## TECHNICAL DATA

### Electrical data

Operating mode	Mains voltage
Mains frequency	50/60 Hz
Power factor $\lambda$	>0.5
Nominal wattage	13.00 W
Nominal voltage	220...240 V
Nominal current	0.063 A
Max. no. of lum. on circuit break. B16 A	75
Max. no. of lum. on circuit break. C10 A	96
Max. no. of lum. on circuit break. C16 A	60


### Photometrical data

Color temperature	3000 K
Luminous efficacy	35 lm/W
Luminous flux	480 lm
Light color (designation)	Warm White
Color rendering index Ra	$\geq 80$
Standard deviation of color matching	<6 sdc <sub>m</sub>

### Light technical data

Beam angle	100.00 °
------------	----------

### Dimensions & weight



Diameter	202.0 mm
Height	45.0 mm
Product weight	770.00 g

### Colors & materials

<b>Product color</b>	Gray
<b>Housing color</b>	Gray
<b>Body material</b>	Aluminum
<b>Cover material</b>	Polycarbonate (PC)

#### Temperatures & operating conditions

<b>Ambient temperature range</b>	-20...+40 °C
----------------------------------	--------------

#### Lifespan

<b>Number of switching cycles</b>	15000
<b>Lifespan L70/B50 at 25 °C</b>	30000 h

#### Additional product data

<b>Mounting type</b>	Surface
<b>Mounting location</b>	Ceiling / Wall



#### Capabilities

<b>Dimmable</b>	No
<b>Type of connection</b>	Screw terminal, 3-Pole
<b>LED module replaceable</b>	Not replaceable

#### Certificates & standards

<b>Type of protection</b>	IP54
<b>Protection class</b>	I
<b>Protection class IK (shock resistance)</b>	IK06
<b>Glow Wire Test according to IEC 60695-2-12</b>	-
<b>Photobio. safety group acc. to EN62471</b>	RG0
<b>Standards</b>	CE

### Light Distribution



LDC typ cone

LDC typ polar

### EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075074897	Folding carton box 1	65 mm x 237 mm x 228 mm	830.00 g	3.51 dm <sup>3</sup>
4058075074903	Shipping carton box 6	470 mm x 255 mm x 215 mm	5254.00 g	25.77 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### REFERENCES / LINKS

For Guarantee see  
 ▶ [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.