

CAT. N° 7 520 70



MOTION SENSOR WITHOUT NEUTRAL VALENA IN'MATIC - SCREW/CLAW MOUNTING

Pack (number of units)	1
Volume (dm ³)	0,677
Weight (g)	138,00

Product characteristics

Motion sensors

- All sensors are compatible with any type of lamp
- Detection field 120°
- Detection range 8 m
- Integrated self-protection against overloads and short-circuits
- Screw terminals

Motion sensor without neutral

- Accepted power by lamp type:
 - LEDs 3 W to 100 W (if several sensors are installed on the same circuit, the minimum load increases : see data sheet)
 - Compact fluorescent 3 W to 100 W (if several sensors are installed on the same circuit, the minimum load increases : see data sheet)
 - LEDs, CFLs, Halogen, fluorescent tubes with ferromagnetic or electronic ballast: 3 VA to 250 VA
 - 230 V halogen, incandescent: 3 W to 250 W
- Up to 3 sensors can be connected in parallel
- Time delay setting from 10 s to 10 min
- Light level threshold setting from 5 lux to 1275 lux
- Standby consumption: 0.02 W

General characteristics

Valena™ IN'MATIC mechanisms - motion sensors, extractible emergency lamp, roller blind control, keycard switches

- Valena In'Matic mechanisms are supplied with metal support, for claw or screw mounting
- To be equipped with Valena Life or Valena Allure cover plates and plates
- Supplied with mounted dust protection transparent shield
- Packaged in boxes

Documentation



Catalogue pages & additional information

- [Description page \(p.497\)](#)
- [Selection chart \(p.509\)](#)
- [Selection chart \(p.513\)](#)



Installation & technical data

- [F01970EN-01](#)



Installation instructions & related documents

- [LE07972AD](#)