



Type of luminaire

| | |
|----------------------------------|---|
| Type of luminaire | Bollard. |
| Photometric body | Uncovered, diffused light with rotationally symmetrical light distribution. |
| Characteristics of the luminaire | Bollard luminaire of stable and durable construction. For lighting private areas and public spaces. |

General information

| | |
|---------------------------------|---|
| Materials | Hot-dip galvanized steel. Lens - plastic PMMA in milky color. Silicone gasket. |
| Mounting method | Fixing of the luminaire: 3 holes $\varnothing 9\text{mm}$ with a diameter of $\varnothing 65\text{mm}$ every 120° . |
| Terminal | Connection terminals: max $3 \times 4\text{mm}^2$, possibility to connect luminaire in loop max $3 \times 2,5\text{mm}^2$. A round wire in the isolation with a diameter of max $\varnothing 12,5\text{mm}$. |
| Type of light source | LED module AC integrated |
| Light control | Phase-dimming (TRIAC). |
| Net / gross weight of luminaire | 7,3kg / 7,3kg |
| Box dimensions [cm] | 21x21,5x5,7 |

Technical data

| | |
|-------------------------------------|-------------------------------|
| LED module | Lumens EDC/47C/10W/830/230V/A |
| Light source wattage | 10W |
| Luminaire wattage | 10W |
| Lamp luminous flux | 900lm |
| Luminaire luminous flux | 294lm |
| Light source efficiency | 90lm/W |
| Efficiency of the luminaire | 29,4lm/W |
| Color temperature | 3000K |
| Colour consistency (McAdam ellipse) | SDCM3 |
| Colour rendering index CRI | 80 |
| Rated life time L70/B50 at 25°C | 50 000h |
| Power Factor luminaire | PF > 0,99 |
| Ta Rated temperature | +25°C |

This product contains light source of energy efficiency class **A+**

| | |
|----------------|--------------------|
| Inrush current | 46,1mA/500 μ s |
|----------------|--------------------|

Accessories sold separately

| | |
|-----------|--------------------|
| 205ZX0010 | Concreting anchor. |
| 206GA0010 | Ground anchor. |
| 206GA0S10 | Anchoring support. |

Spare parts

| | |
|--------------|--------------|
| 06295000 | Lens. |
| 08295000 | Gasket. |
| 46999366 | LED module. |
| ZS1260zx0011 | Service set. |

Files to download

| | |
|-----------------------|-----------------------|
| Photometric LDT files | Photometric IES files |
| Manual | |

Indexes

| Index | Color | RAL |
|--------|------------|------|
| 1260B | BLACK | 9005 |
| 1260GA | GALVANIZED | - |