



Type of luminaire	
Type of luminaire	Wall luminaire.
Photometric body	Single-sided light facing down.
Characteristics of the luminaire	A luminaire with a wide range of applications, for illuminating wall and facade surfaces and other architectural concepts

General information	
Materials	Powder painted aluminum cast. Lens - transparent polycarbonate with structure, UV stabilized. Silicone gasket. EPDM cable gland.
Mounting method	Fixing of the luminaire: mounting plate, 2 adjustment holes 5x10mm, 45mm spacing, directly 2 ø5mm holes, 68mm spacing
Terminal	Connection terminals: max 3x2.5mm ² , possibility to connect the luminaire in loops, max 3x1.5mm ² . Round insulated cable with a diameter of ø7 ... 10.5mm
Type of light source	LED module, power supply
Light control	Trailing edge dimming
Net / gross weight of luminaire	2,62kg / 2,98kg
Box dimensions [cm]	34,5x15x17

Technical data	
2 LED modules	Philips Strip OC 0.5ft 550lm 8xx FC LV5 (Datasheet)
Driver	Philips Xitanium 8W 0,2A 40V TE SC 230V (Datasheet)
Light source wattage	6,6 W
Luminaire wattage	8,4W
Lamp luminous flux	1128lm
Luminaire luminous flux	732lm
Light source efficiency	170,9lm/W
Efficiency of the luminaire	87,1lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>70 000h
LED photobiological threat	RG0 or RG1
Power Factor luminaire	PF > 0,9
THD factor	< 20%
Ta Rated temperature	+25°C

This product contains light sources of energy efficiency class **A++**

Inrush current	1,65A/16,5µs
----------------	--------------

Spare parts	
ZS1308zx0010	Service set.

Files to download	
Photometric LDT files	Photometric IES files
Manual	BIM Revit
BIM ArchiCAD	

Indexes		
Index	Color	RAL
1308AL	ALUMINIUM	9006
1308B	BLACK	9005
1308GR	GRAPHITE	7016
1308W	WHITE	9003