



## Type of luminaire

Type of luminaire	Accessories
Photometric body	Single-sided, symmetric light facing down.
Characteristics of the luminaire	Pole luminaire with 2160mm high (two-part luminaire). For lighting private areas, public spaces and other architectural concepts.

## General information

Materials	Extruded aluminum profile, powder coated. Lens - transparent polycarbonate with structure, UV stabilized. Silicone gasket.
Mounting method	Fixing of the luminaire: 4 holes on a diameter $\phi$ 12mm, spacing 200x200mm. Art. 1360: 2-parts pole luminaire. Other accessories need to be purchased separately.
Terminal	Connection terminals: max 3x2,5mm <sup>2</sup> , possibility to connect luminaire in loop max 3x2,5mm <sup>2</sup> . A round wire in the isolation with a diameter of max $\phi$ 12,5mm.
Type of light source	LED module AC integrated
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	10,54kg / 12,11kg
Box dimensions [cm]	25x115x56
Side area of luminaire	0,232m <sup>2</sup>

## Technical data

2 LED modules	Lumens LNM/280X30/9W/830/230V
External control	Dimmers Lumens LED AC (User manual)
Light source wattage	18W
Luminaire wattage	18W
Lamp luminous flux	1710lm
Luminaire luminous flux	962lm
Light source efficiency	95lm/W
Efficiency of the luminaire	53,4lm/W
ULOR	0%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
Power Factor luminaire	PF > 0,99
THD factor	< 20%
Ta Rated temperature	+25°C
Max ambient temperature	-30...+25°C

This product contains light sources of energy efficiency class **A+**

Inrush current	108,8mA/500 $\mu$ s
----------------	---------------------

## Accessories sold separately

116ZX0009	Concreting anchor ( anchor L190mm).
117GA0009	Ground anchor.
118GA0009	Anchoring support.
119ZX0009	Concreting anchor ( anchor L700mm).
7666ZX0009	Connection box with fuse 5x20mm

## Spare parts

06136000	Lens.
08136000	Gasket.
ZS1360zx0010	Service set.

## Files to download

Photometric LDT files	Photometric IES files
Manual	BIM Revit
BIM ArchiCAD	



## Indexes

Index	Color	RAL
1360AL	ALUMINIUM	9006
1360B	BLACK	9005
1360GR	GRAPHITE	7016