



## Type of luminaire

Type of luminaire	Wall luminaire.
Photometric body	Double-sided light facing up and down.
Characteristics of the luminaire	Wall-mounted luminaire with modern design. For lighting private areas and public spaces.

## General information

Materials	Base - galvanized steel. Front - galvanized steel or powder coated galvanized steel. Lens - safety glass, transparent. Silicone gasket.
Mounting method	Fixing of the luminaire: 2 holes $\varnothing$ 4,2mm, spacing 45mm.
Terminal	Connection terminals: max 3x2,5mm <sup>2</sup> , possibility to connect luminaire in loop max 3x1,5mm <sup>2</sup> . A round wire in the isolation with a diameter of $\varnothing$ 7...10,5mm.
Type of light source	LED Gu10 lamp, 25D
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	1,45kg / 1,45kg
Box dimensions [cm]	20x13x9,5

## Technical data

2 LED GU10 lamps.	Philips Master LED ExpertColor 25D 3,9W=> 35W Gu10
Light source wattage	7,8W
Luminaire wattage	7,8W
Lamp luminous flux	530lm
Luminaire luminous flux	500lm
Light source efficiency	67,9lm/W
Efficiency of the luminaire	64,1lm/W
Color temperature	2700K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	97
Rated life time L70/B50 at 25°C	40 000h
Power Factor luminaire	PF 0,8
Ta Rated temperature	+25°C

This product contains light sources of energy efficiency class **A+**

## Recommended light sources

Osram LED Parathom Advanced / Pro max 4W PAR16 Gu10 Philips Master LED max 4W PAR16 Gu10

## Spare parts

46102507 LED Gu10 lamp.

## Files to download

Photometric LDT files Photometric IES files  
Manual BIM ArchiCAD

## Indexes

Index	Color	RAL
1370B	BLACK	9005
1370GA	GALVANIZED	-