



## Type of luminaire

Type of luminaire	Wall luminaire.
Photometric body	Single-sided, symmetric light facing down.
Characteristics of the luminaire	Wall-mounted luminaire with modern design. For lighting private areas and public spaces.

## General information

Materials	Base - galvanized steel. Front - galvanized steel or powder coated galvanized steel. Lens - safety glass, transparent. Silicone gasket. EPDM cable gland.
Mounting method	Fixing of the luminaire: 2 holes $\varnothing 4,2\text{mm}$ , spacing 45mm.
Terminal	Connection terminals: max $3 \times 2,5\text{mm}^2$ , possibility to connect luminaire in loop max $3 \times 1,5\text{mm}^2$ . A round wire in the isolation with a diameter of $\varnothing 7 \dots 10,5\text{mm}$ .
Type of light source	LED Gu10 lamp
Net / gross weight of luminaire	0,85kg / 0,93kg
Box dimensions [cm]	12,5x13x10

## Technical data

LED GU10 lamp	LED PAR16
Light source wattage	MAX 4W
Lamp luminous flux	~ 265lm
Light source efficiency	66,3lm/W
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class **A+**

Possibility to order luminaire with LED GU10 lamp type Philips Master LED ExpertColor 256lm/3,9W/2700K/25D (dimnable).

## Accessories sold separately

46102507	LED GU10 lamp.
----------	----------------

## Recommended light sources

Osram LED Parathom Advanced / Pro max 4W PAR16 Gu10      Philips Master LED max 4W PAR16 Gu10

## Files to download

Photometric LDT files	Photometric IES files
Manual	BIM ArchiCAD

## Indexes

Index	Color	RAL
1374B	BLACK	9005
1374GA	GALVANIZED	-