



Type of luminaire

Type of luminaire	Bollard.
Photometric body	Light with rotationally symmetrical light distribution.
Characteristics of the luminaire	Modern design luminaire. For lighting gardens, private areas and public spaces.

General information

Materials	Powder painted aluminum cast. Lens - satin PMMA plastic. Silicone gasket. Nylon6 cable gland.
Mounting method	Fixing of the luminaire: 3 holes $\varnothing 9\text{mm}$ on a diameter $\varnothing 65\text{mm}$ every 120° .
Terminal	Connection terminals: max $2 \times 2,5\text{mm}^2$, possibility to connect in loop max $2 \times 2,5\text{mm}^2$. A round wire in the isolation with a diameter of $\varnothing 8 \dots 12,5\text{mm}$.
Type of light source	LED E27 lamp
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	4,83kg / 5,81kg
Box dimensions [cm]	16x16x93

Technical data

LED E27 lamp	Philips Master LEDbulb 806lm/8,5W/2700K (sciemnialna).
Light source wattage	8,5W
Luminaire wattage	8,5W
Lamp luminous flux	$\sim 806\text{lm}$
Luminaire luminous flux	495lm
Light source efficiency	94,8lm/W
Efficiency of the luminaire	58,2lm/W
Color temperature	2700K
Colour consistency (McAdam ellipse)	SDCM6
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	25 000h
Power Factor luminaire	PF 0,7
Ta Rated temperature	$+25^\circ\text{C}$

This product contains light source of energy efficiency class **A+**

Accessories sold separately

205ZX0010	Concreting anchor.
206GA0010	Ground anchor.
206GA0S10	Anchoring support.

Recommended light sources

Osram LED Parathom Classic / Retrofit E27 Philips Master LEDbulb / Classic / CorePro E27

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
1382AL	ALUMINIUM	9006
1382GR	GRAPHITE	7016