



## Type of luminaire

Type of luminaire	Wall luminaire.
Photometric body	Single-sided light facing down.
Characteristics of the luminaire	Wall luminaire with 220 ... 240V electricity distributor. For lighting private areas and other applications

## General information

Materials	Base - galvanized steel. Front - galvanized steel or powder coated galvanized steel. Lens - transparent polycarbonate with structure, UV stabilized. Silicone gasket.
Mounting method	Fixing the luminaire: 2 holes $\varnothing 4.2\text{mm}$ , spacing 122mm
Terminal	Connection terminals: max $3 \times 2.5\text{mm}^2$ . Round insulation cable with a diameter of $\varnothing 7 \dots 10.5\text{mm}$
Type of light source	LED module, power supply
Light control	Trailing edge dimming

## Technical data

LED module	Philips Strip OC 0.5ft 550lm 8xx FC HV5 (Datasheet)
Driver	Philips Xitanium 7W 0,35A 20V TE SC 230V (Datasheet)
Light source wattage	4W
Luminaire wattage	5,1W
Lamp luminous flux	653lm
Luminaire luminous flux	371lm
Light source efficiency	163,3lm/W
Efficiency of the luminaire	72,7lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>70 000h
Power Factor luminaire	PF 0,96
THD factor	< 20%
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class **A++**

Inrush current	1A/15,2 $\mu$ s
----------------	-----------------

## Maximum number of luminaires of this type per MCB:

**B 10A:** 157, **B 16A:** 250, **C 10A:** 260, **C 16A:** 425

## Spare parts

ZS1391zx0011	Service set.
--------------	--------------

## Files to download

Photometric LDT files	Photometric IES files
Manual	BIM Revit
BIM ArchiCAD	

## Indexes

Index	Color	RAL
1391B	BLACK	9005
1391GA	GALVANIZED	-