




## 

Halmstad 1410XX0010 23.07.2021 v.10.1 www.norlys.com









Type of luminaire		
Type of lumianire	Bollard.	
Photometric body	Uncovered light, partly covered from the top.	
Characteristics of the luminaire	Bollard luminaire of stable and durable construction. For lighting private areas and public spaces.	

General information	
Materials	Wood - scandinavian painted pine and hot-dip galvanized steel. Wood - scandinavian painted pine, hot-dip galvanized and powder painted steel. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Fixing of the luminaire: 3 holes ø9mm with a diameter of ø65mm every 120 °.
Terminal	Connection terminals: max 3x2,5mm², possibility to connect luminaire in loop max 3x1,5mm². A round wire in the isolation with a diameter of max ø12,5mm.
Type of light source	E27 lamp
Net weight of luminaire	8,44kg
Box dimensions [cm]	15x15x91

Technical data		
E27 lamp	QA55 / LED A5560	
Light source wattage	MAX 46W / LED 9W	
Ta Rated temperature	+25°C	

This product contains light source of energy efficiency class A+ D

Possibility to order the luminaire with LED E27 Philips Master LEDbulb 806lm / 8,5W / 2700K (dimmable).

Recommended light sources		
Osram LED Parathom Classic E27	Philips Master LEDbulb / Ledbulb Classic E27	
Osram ECO PRO Classic 46<=>60W E27	Philips ECO Classic 42<=>60W E27	

Spare parts	
06295000	Lens.
08295000	Gasket.

## Files to download Photometric LDT files Photometric IES files 3D models and drawings Manual BIM ArchiCAD

Indexes		
Index	Color	RAL
1410B	BLACK	9005
1410GA	GALVANIZED	-





