



Type of luminaire

Type of luminaire	Bollard.
Photometric body	Uncovered light, partly covered from the top.
Characteristics of the luminaire	Bollard luminaire of stable and durable construction. For lighting private areas and public spaces.

General information

Materials	Wood - scandinavian impregnated pine and hot-dip galvanized steel. Wood - scandinavian impregnated pine, hot-dip galvanized and powder painted steel. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Fixing of the luminaire: 3 holes $\varnothing 9\text{mm}$ with a diameter of $\varnothing 65\text{mm}$ every 120° .
Terminal	Connection terminals: max $3 \times 2,5\text{mm}^2$, possibility to connect luminaire in loop max $3 \times 1,5\text{mm}^2$. A round wire in the isolation with a diameter of max $\varnothing 12,5\text{mm}$.
Type of light source	E27 lamp
Net / gross weight of luminaire	7,75kg / 8,75kg
Box dimensions [cm]	93x16x16

Technical data

E27 lamp	QA55 / LED A55..60
Light source wattage	MAX 46W / LED 9W
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class **A+ D**

Possibility to order the luminaire with LED E27 Philips Master LEDbulb 806lm / 8,5W / 2700K (dimmbale).

Recommended light sources

Osram LED Parathom Classic E27	Philips Master LEDbulb / Ledbulb Classic E27
Osram ECO PRO Classic 46<=>60W E27	Philips ECO Classic 42<=>60W E27

Spare parts

06295000	Lens.
08295000	Gasket.

Files to download

Photometric LDT files	Photometric IES files
Manual	BIM ArchiCAD

Indexes

Index	Color	RAL
1413B	BLACK	9005
1413GA	GALVANIZED	-