



## Type of luminaire

Type of luminaire	Bollard.
Photometric body	Uncovered, diffused light with rotationally symmetrical light distribution.
Characteristics of the luminaire	Bollard luminaire of stable and durable construction. For lighting private areas and public spaces.

## General information

Materials	Hot-dip galvanized steel. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Fixing of the luminaire: 3 holes $\varnothing 9\text{mm}$ with a diameter of $\varnothing 65\text{mm}$ every $120^\circ$ .
Terminal	Connection terminals: max $3 \times 2,5\text{mm}^2$ , possibility to connect luminaire in loop max $3 \times 2,5\text{mm}^2$ . A round wire in the isolation with a diameter of max $\varnothing 12,5\text{mm}$ .
Type of light source	LED E27 lamp
Net / gross weight of luminaire	9,75kg / 11,05kg
Box dimensions [cm]	15x15x91

## Technical data

LED E27 lamp	Philips Master LEDbulb 806lm/8,5W/2700K (ściemnialna)
Light source wattage	8,5W
Luminaire wattage	8,5W
Lamp luminous flux	~ 806lm
Color temperature	2700K
Colour consistency (McAdam ellipse)	SDCM6
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	25 000h
Power Factor luminaire	PF 0,7
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class **A+**

## Accessories sold separately

205ZX0010	Concreting anchor.
206GA0010	Ground anchor.
46999021	LED E27 lamp.

## Recommended light sources

Osram LED Parathom Classic E27 Philips Master LEDbulb / Ledbulb Classic E27

## Spare parts

06281004	Lens.
08120001	Gasket.

## Files to download

Photometric LDT files Photometric IES files

Manual

## Indexes

Index	Color	RAL
1464B	BLACK	9005
1464GA	GALVANIZED	-