Завантажено з mamadecor.ua

Arendal 1560XX0012 23.07.2021 v.12.7 www.norlys.com

ARENDAL 1560 IP 55 65 220-240V 50-60Hz C€ [ER[E27

Type of lumianire	Bollard.
Photometric body	Uncovered light.
Characteristics of the luminaire	Modern design luminaire with a combination of decorative crystal lampshade and durable and stable casing
General information	
Materials	Hot-dip galvanized and powder-coated steel. Lens - crystal glass, satin inside. Lens may change to light amber colour over time.
Mounting method	Fixing of the luminaire: 3 holes ø9mm with a diameter of ø65mm every 120°.
Terminal	Connection terminals: max 3x4mm², possibility to connect luminaire in loop max 3x2,5mm². Round insulated cable with a diameter of max ø12,5mm.
Type of light source	E27 lamp
Net / gross weight of luminaire	14,26kg / 15,71kg
Box dimensions [cm]	97x18,5x18,5

E27 lamp	QA55 / LED A5560	
Light source wattage	max 46W / LED 9W	
Ta Rated temperature	+25°C	

This product contains light source of energy efficiency class A+

Possibility to order the luminaire with LED E27 Philips Master LEDbulb 806lm / 8,5W / 2700K (dimmable).

Accessories sold separately		
205ZX0010	Concreting anchor	
206GA0010	Ground anchor	
206GA0S10	Anchoring support	
46999021	LED E27 lamp	

Recommended light sources

Osram LED Parathom Classic E27 Osram ECO PRO Classic 46<=>60W E27

Lens.

Philips Master LEDbulb / Ledbulb Classic E27 Philips ECO Classic 42<=>60W E27

Spare parts

915600229	

Files to download

Manual

Indexes		
Index	Color	RAL
1560B	BLACK	9005
1560GA	GALVANIZED	-
1560GR	GRAPHITE	7016










Please read the manual before installing it. Due to the dynamic development of lighting technology, additional information is available upon request. LED modules must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire. ordance with



120

