



## Type of luminaire

Type of luminaire	Wall luminaire.
Photometric body	Diffused, uncovered light.
Characteristics of the luminaire	Scandinavian design luminaire. For lighting gardens, private areas and public spaces.

## General information

Materials	Base - powder painted aluminum cast. Front - hot-dip galvanized steel, powder painted steel. Lens - milky polycarbonate, UV stabilized. Silicone gasket.
Mounting method	Fixing of the luminaire: 2 holes $\varnothing$ 5mm, spacing 80x80mm.
Terminal	Fixing of the luminaire: max. $3 \times 2,5\text{mm}^2$ , possibility to connect luminaire in loop max. $3 \times 1,5\text{mm}^2$ . A round wire in the isolation with a diameter $\varnothing 7 \dots 10,5\text{mm}$ .
Type of light source	LED module AC integrated
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	2,7kg / 2,85kg
Box dimensions [cm]	21,5x14x24

## Technical data

LED module	Lumens EDC 57C 8W xxx 230V A FF Ver.1.0 (Datasheet)
Light source wattage	8W
Luminaire wattage	8W
Lamp luminous flux	890lm
Luminaire luminous flux	332lm
Light source efficiency	111,3lm/W
Efficiency of the luminaire	41,5lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
LED photobiological threat	RG0 or RG1
Power Factor luminaire	PF > 0,99
THD factor	< 20%
Ta Rated temperature	+25°C
Max ambient temperature	-35...+25°C

This product contains light source of energy efficiency class **A+**

Inrush current	2,9A/34 $\mu$ s
----------------	-----------------

## Spare parts

06220000	Lens.
08550005	Gasket.
46999552	LED module.

## Files to download

Photometric LDT files	Photometric IES files
Manual	

## Indexes

Index	Color	RAL
1600B	BLACK	9005
1600GA	GALVANIZED	-