



Type of luminaire	
Type of luminaire	In-ground luminaire.
Photometric body	Four side light distribution covered from the top.
Characteristics of the luminaire	An orientation luminaire that can be driven on by vehicles with pneumatic tires. Luminaires should not be used on traffic lanes where they would be exposed to horizontal weight load as a result of sudden braking, acceleration, and change of direction

General information	
Materials	Powder painted aluminum cast. Lens - satin polycarbonate, UV stabilized . Silicone gasket. Nickel plated brass cable gland.
Mounting method	Fixing of the luminaire: 3 holes $\varnothing 4,5\text{mm}$ on a diameter $\varnothing 100\text{mm}$ every 120° connected to the assembly box, or to appropriately prepared hole in the wood (see manual). Other accessories sold separately
Terminal	Luminaire equipped with 05RN8-F 3G1 cable with a length of 3m. For a connection in an appropriately selected electrical installation box. Maximum load of 1000kg
Type of light source	LED Gu10 lamp
Net / gross weight of luminaire	1kg / 1,25kg
Box dimensions [cm]	15,6x15,6x19,4

Technical data	
Light source wattage	max 6W
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class **A+**

It is possible to order the luminaire together with the Gu10 LED lamp MASTER LED type Philips ExpertColor 5.5-50W GU10 930 36D (dimnable)

Accessories <small>sold separately</small>	
143ZX0009	Power cord cover
145ZX0009	Hermetic 3-track box
146ZX0009	Hermetic 8-track box
46102506	LED Gu10 lamp

Recommended light sources	
Osram LED Parathom max 6W \Leftrightarrow 50W PAR16 Gu10	Philips Master LED max 6W \Leftrightarrow 50W PAR16 Gu10

Spare parts	
06155010	Lens.
08155000	Gasket.
915500121	Front.

Files to download	
Photometric LDT files	Photometric IES files
Manual	BIM ArchiCAD

Indexes		
Index	Color	RAL
1630B	BLACK	9005
1630GR	GRAPHITE	7016