



## Type of luminaire

Type of luminaire	Wall luminaire.
Photometric body	Double-sided light facing up and down.
Characteristics of the luminaire	Luminaire with a wide range of applications for example for illumination of walls and facade surfaces or any other architectural concepts.

## General information

Materials	Base - powder painted aluminum cast. Body - hot-dip galvanized steel Lens - transparent polycarbonate with structure, UV stabilized. Silicone gasket.
Mounting method	Fixing of the luminaire: 2 holes $\varnothing$ 4,5mm, spacing 180x60mm.
Terminal	Connection terminals: max 3x2,5mm <sup>2</sup> , possibility to connect luminaire in loop max 3x1,5mm <sup>2</sup> . A round wire in the isolation with a diameter of $\varnothing$ 7...10,5mm.
Type of light source	E27 lamp
Net / gross weight of luminaire	1,45kg / 1,6kg
Box dimensions [cm]	24x12x9,5

## Technical data

E27 lamp	QA55 / LED A55..60
Light source wattage	max 46W / LED 9W
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class **A+ D**

Possibility to order the luminaire with LED E27 Philips Master LEDbulb 806lm / 8,5W / 2700K (dimnable).

## Accessories sold separately

46999021	LED E27 lamp.
----------	---------------

## Recommended light sources

Osram LED Parathom Classic E27	Philips Master LEDbulb / Ledbulb Classic E27
Osram ECO PRO Classic 46<=>60W E27	Philips ECO Classic 42<=>60W E27

## Files to download

Photometric LDT files	Photometric IES files
Manual	BIM Revit
BIM ArchiCAD	

## Indexes

Index	Color	RAL
1702GA	GALVANIZED	-