



Type of luminaire	
Type of luminaire	Wall luminaire.
Photometric body	Single-sided light facing down.
Characteristics of the luminaire	Luminaire with a wide range of applications for example for illumination of walls and facade surfaces or any other architectural concepts.

General information	
Materials	Front - hot-dip galvanized steel. Body - powder painted aluminum cast Lens - transparent polycarbonate with structure, UV stabilized. Silicone gasket. EPDM cable gland.
Mounting method	Fixing of the luminaire: mounting plate with 2 adjust holes 5x10mm, spacing 45mm, directly 2 holes ø5mm, spacing 68mm.
Terminal	Connection terminals: max 3x2,5mm ² , possibility to connect luminaire in loop max 3x1,5mm ² . A round wire in the isolation with a diameter of ø7...10,5mm.
Type of light source	E27 lamp
Box dimensions [cm]	31,5x14x16

Technical data	
E27 lamp	QA55 / LED A55..60
Light source wattage	MAX 46W / LED 9W
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class **A+ D**
Possibility to order luminaire with LED E27 lamp, type Philips Master LEDbulb 806lm/8,5W/2700K (dimnable).

Accessories <small>sold separately</small>	
46999021	LED E27 lamp.

Recommended light sources	
Osram ECO PRO Classic 46<=>60W E27	Philips ECO Classic 42<=>60W E27
Osram LED Parathom Classic / Retrofit E27	Philips Master LEDbulb / Classic / CorePro E27

Spare parts	
08120006	Gasket.

Files to download	
Photometric LDT files	Photometric IES files
BIM Revit	BIM ArchiCAD

Indexes		
Index	Color	RAL
1717GA	GALVANIZED	-