




Stockholm 220XX0010 23.07.2021 v.10.2 www.norlys.com





Type of luminaire	uminaire	
Type of lumianire	Wall luminaire.	
Photometric body	Diffused, uncovered light.	
Characteristics of the luminaire	Plafon type luminaire in scandinavian design. For lighting gardens, private areas and public spaces.	

General information	eneral information		
Materials	Base - powder painted aluminum cast. Hot-dip galvanized and powder-coated steel. Lens - milky polycarbonate, UV stabilized. Silicone gasket.		
Mounting method	Fixing of the luminaire: 2 holes ø5mm, spacing 80x80mm.		
Terminal	Connection terminals: max 3x2,5mm², possibility to connect luminaire in loop max 3x2,5mm². A round wire in the isolation with a diameter of ø710,5mm.		
Type of light source	E27 lamp		
Net / gross weight of luminaire	2,5kg / 2,7kg		
Box dimensions [cm]	22x15,5x25		
Mounting method Terminal Type of light source Net / gross weight of luminaire	Fixing of the luminaire: 2 holes ø5mm, spacing 80x80mm. Connection terminals: max 3x2,5mm², possibility to connect luminaire in loc max 3x2,5mm². A round wire in the isolation with a diameter of ø710,5mm E27 lamp 2,5kg / 2,7kg		

Technical data	nical data	
E27 lamp	QA55 / LED A5560	
Light source wattage	MAX 46W / LED 9W	
Ta Rated temperature	+25°C	

This product contains light source of energy efficiency class A+ D

Possibility to order the luminaire with LED E27 Philips Master LEDbulb 806lm / 8,5W / 2700K (dimmable).

Recommended light sources		
Osram LED Parathom Classic E27	Philips Master LEDbulb / Ledbulb Classic E27	
Osram ECO PRO Classic 46<=>60W E27	Philips ECO Classic 42<=>60W E27	

Spare parts	
06220000	Lens.
08550005	Gasket.

Files to download

Manual

Indexes		
Index	Color	RAL
220B	BLACK	9005
220GA	GALVANIZED	-



