





Stockholm 283XX0309 23.07.2021 v.09.1 www.norlys.com



Max.2520 Min.1740	920	Ø350
Max.		





Type of luminaire	
Type of lumianire	Accessories
Photometric body	Uncovered light.
Characteristics of the luminaire	Pole top luminaire in scandinavian design. For installation on a lighting pole with adjustable height 17402520mm. For lighting gardens, parks, and any other architectural concepts.

	otner architectural concepts.	
General information		
Materials	Hot-dip galvanized steel. Powder painted steel. Lens - transparent plastic PMMA.	
Mounting method	Fixing of the luminaire: 3 holes Ø10,5 on a diameter Ø270mm every 120°. Set contains: art.2017- luminaire art. 3009/3011- lighting pole Other accessories need to be purchased separately.	
Terminal	Connection terminals: max 4x2,5mm², possibility to connect luminaire in loop max 4x2,5mm². A round wire in the isolation on diameter ø712,5mm.	
Type of light source	E27 lamp	

Technical data		
E27 lamp	QA55 / LED A5560	
Light source wattage	2x max 77W / LED 9W	
This product contains light source of energy efficiency class A+ D		

Accessories sold separately		
405ZX0009	Concreting anchor.	

403ZX0003		Concreting anchor.		
	406ZX0009	Ground anchor.		
Recommended light sources Philips Master LEDbulb / Classic / CorePro E27 Osrar				
		Osram ECO PRO Classic 77<=>100W E27		

· · · · · · · · · · · · · · · · · · ·	
Philips ECO Classic 70<=>100W E27	Philips Master LEDbulb / LEDbulb Classic E27
Spare parts	

opare parts	
06281002	Lens.
08281001	Gasket.
Files to download	

Photometric LDT files	Photometric IES files

Indexes		
Index	Color	RAL
283B	BLACK	9005
283GA	GALVANIZED	-





