



Type of luminaire	
Type of luminaire	Bollard.
Photometric body	Uncovered, diffused light with rotationally symmetrical light distribution.
Characteristics of the luminaire	Bollard luminaire of stable and durable construction. For lighting private areas and public spaces.

General information	
Materials	Hot-dip galvanized steel. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Fixing of the luminaire: 3 holes $\varnothing 9\text{mm}$ with a diameter of $\varnothing 56\text{mm}$ every 120° .
Terminal	Connection terminals: max $3 \times 2,5\text{mm}^2$. A round wire in the isolation with a diameter of max $\varnothing 12\text{mm}$.
Type of light source	E27 lamp
Net / gross weight of luminaire	4,45kg / 4,85kg
Box dimensions [cm]	32x20x20

Technical data	
E27 lamp	QA55 / LED A55..60
Light source wattage	max 46W / LED 9W
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class **A+ D**

Accessories <small>sold separately</small>	
205ZX0010	Concreting anchor.
206GA0010	Ground anchor.
206GA0S10	Anchoring support.

Recommended light sources	
Osram LED Parathom Classic E27	Philips Master LEDbulb / Ledbulb Classic E27
Osram ECO PRO Classic 46<=>60W E27	Philips ECO Classic 42<=>60W E27

Spare parts	
06281004	Lens.
08288004	Gasket.

Files to download	
Photometric LDT files	Photometric IES files

Indexes		
Index	Color	RAL
299B	BLACK	9005
299GA	GALVANIZED	-