



Type of luminaire	
Type of luminaire	Bollard.
Photometric body	Indirect light with rotationally symmetrical light distribution facing down.
Characteristics of the luminaire	Bollard luminaire of stable and durable construction. For lighting private areas and public spaces

General information	
Materials	Powder painted aluminum cast. Lens - clear polycarbonate, UV stabilized. Silicone gasket. Nylon6 cable gland.
Mounting method	Mounting of the luminaire: 3 holes ø9mm with a diameter of ø145mm every 120°
Terminal	Connection terminals: max 3x4mm², Possibility to connect luminaire in loop max 3x2,5mm², Round insulated cable with a diameter of ø8...17mm
Type of light source	LED module, power supply
Light control	Trailing edge dimming
Net / gross weight of luminaire	11,03kg / 12,69kg
Box dimensions [cm]	22,5x22,5x103,5

Technical data	
LED module	1305003G2 Cree XD16 4000K
Driver	Philips Xitanium 10W 0,5A 20V TE SC
Light source wattage	9,6W
Luminaire wattage	12,2W
Lamp luminous flux	1171lm
Luminaire luminous flux	493lm
Light source efficiency	122lm/W
Efficiency of the luminaire	40,4lm/W
Color temperature	4000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
Power Factor luminaire	PF > 0,98
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class **A+**

Inrush current	3,36A / 36µs
----------------	--------------

Accessories <small>sold separately</small>	
1230ZX0009	Concreting anchor
1231GA0009	Ground anchor
1232GA0009	Anchoring support

Spare parts	
4699102101	LED module.
46999697	Power supply.

Files to download	
Photometric LDT files	Photometric IES files
Manual	

Indexes		
Index	Color	RAL
5008AL	ALUMINIUM	9006
5008GR	GRAPHITE	7016