



Type of luminaire

| | |
|----------------------------------|---|
| Type of luminaire | Wall luminaire. |
| Photometric body | Single-sided light with 62° beam angle facing down. |
| Characteristics of the luminaire | A luminaire with a wide range of applications, among others for lighting: wall and facade surfaces and other architectural concepts |

General information

| | |
|---------------------------------|---|
| Materials | Powder painted aluminum cast. Lens - safety glass, transparent. Silicone gasket. EPDM cable gland. |
| Mounting method | Mounting of the luminaire: 2 holes ø7mm, spacing 100x80mm |
| Terminal | Connection terminals: max 3x2,5mm ² , Possibility to connect the luminaire in loops, max 3x1,5mm ² , Round insulated cable with a diameter of ø7 ... 10,5mm |
| Type of light source | LED module, power supply Replaceable (LED only) light source by a professional. Replaceable control gear by a professional. |
| Light control | Non-dimmable luminaire |
| Net / gross weight of luminaire | 5,1kg / 5,1kg |
| Box dimensions [cm] | 22,5x19,5x32 |

Technical data

| | |
|-------------------------------------|--|
| 2 LED modules | Cree JK3030 no.1805004 (Datasheet) |
| Driver | Philips Xitanium 10W 0,5A 20V TE SC 230V (Datasheet) |
| Light source wattage | 9W |
| Luminaire wattage | 11,8W |
| Lamp luminous flux | 1284lm |
| Light source efficiency | 142,7lm/W |
| Color temperature | 4000K |
| Colour consistency (McAdam ellipse) | SDCM3 |
| Colour rendering index CRI | 80 |
| Rated life time L70/B50 at 25°C | 50 000h |
| Power Factor luminaire | PF 0,9 |
| THD factor | 20% |
| Ta Rated temperature | +25°C |

This product contains light sources of energy efficiency class **A++**

| | |
|----------------|--------------|
| Inrush current | 3,36A / 36µs |
|----------------|--------------|

Spare parts

| | |
|--------------|--------------|
| ZS5034zx0G09 | Service set. |
|--------------|--------------|

Files to download

| | |
|--------------|-----------|
| Manual | BIM Revit |
| BIM ArchiCAD | |

Indexes

| Index | Color | RAL |
|--------|-----------|------|
| 5034AL | ALUMINIUM | 9006 |
| 5034GR | GRAPHITE | 7016 |