



| Type of luminaire | |
|----------------------------------|---|
| Type of luminaire | Bollard. |
| Photometric body | Light with rotationally symmetrical light distribution. |
| Characteristics of the luminaire | Modern design luminaire. For lighting gardens and other private and public areas. |

| General information | |
|---------------------------------|--|
| Materials | Powder painted aluminum cast. Lens - transparent plastic PMMA. Silicone gasket. Nylon6 cable gland. |
| Mounting method | Fixing of the luminaire: 3 holes of $\varnothing 9\text{mm}$ on a diameter of $\varnothing 65\text{mm}$ every 120° . The luminaire is equipped with TH-35 rail with a length of 70mm. |
| Terminal | Connection terminals: max $5 \times 4\text{mm}^2$, possibility to connect luminaire in loop max $5 \times 4\text{mm}^2$. A round wire in the isolation with a diameter $\varnothing 8 \dots 17\text{mm}$. |
| Type of light source | LED module AC integrated |
| Light control | Phase-dimming (TRIAC). |
| Net / gross weight of luminaire | 5,5kg / 6,51kg |
| Box dimensions [cm] | 15x15x91 |

| Technical data | |
|-------------------------------------|------------------------------|
| LED module | LUMENS LED DLM90C/230V/A 840 |
| Light source wattage | 10W |
| Luminaire wattage | 10W |
| Lamp luminous flux | 1120lm |
| Light source efficiency | 112lm/W |
| Color temperature | 4000K |
| Colour consistency (McAdam ellipse) | SDCM3 |
| Colour rendering index CRI | 80 |
| Rated life time L70/B50 at 25°C | 50 000h |
| Power Factor luminaire | PF >0,90 |
| Ta Rated temperature | +25°C |

This product contains light source of energy efficiency class **A+**

| | |
|----------------|---------------------|
| Inrush current | 150mA / 500 μ s |
|----------------|---------------------|

| Accessories <small>sold separately</small> | |
|--|--------------------|
| 205ZX0010 | Concreting anchor. |
| 206GA0010 | Ground anchor. |
| 206GA0S10 | Anchoring support. |

| Spare parts | |
|-------------|---------------|
| 0951170000 | Electric set. |

| Files to download | |
|-------------------|-----------|
| Manual | BIM Revit |
| BIM ArchiCAD | |

| Indexes | | |
|---------|-----------|------|
| Index | Color | RAL |
| 5117AL | ALUMINIUM | 9006 |
| 5117GR | GRAPHITE | 7016 |