



Type of luminaire

Type of luminaire	Wall/ceiling luminaire.
Photometric body	Diffused, uncovered light.
Characteristics of the luminaire	Modern design plafond type luminaire.

General information

Materials	Powder painted aluminum cast. Lens - milky polycarbonate, UV stabilized. Silicone gasket. EPDM cable gland.
Mounting method	Fixing of the luminaire: 2 holes \varnothing 5mm, spacing 100x170mm.
Terminal	Connection terminals: max 3x2,5mm ² , possibility to connect luminaire in loop max 3x1,5mm ² . A round wire in the isolation with a diameter of \varnothing 7...10,5mm.
Type of light source	LED module AC integrated
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	1,41kg / 1,93kg
Box dimensions [cm]	29,5x29,5x9,5

Technical data

LED module	LUMENS LED DLM90C/230V/A 840
Light source wattage	10W
Luminaire wattage	10W
Lamp luminous flux	1120lm
Luminaire luminous flux	507lm
Light source efficiency	112lm/W
Efficiency of the luminaire	50,7lm/W
Color temperature	4000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
Power Factor luminaire	PF > 0,9
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class **A+**

Inrush current	150mA/500 μ s
----------------	-------------------

Spare parts

06522002	Lens.
46999401	LED module.
63522001	Gasket.

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
5121AL	ALUMINIUM	9006
5121GR	GRAPHITE	7016
5121W	WHITE	9003