



Type of luminaire

Type of luminaire	Recessed wall luminaire.
Photometric body	Covered light facing down.
Characteristics of the luminaire	The luminaire is adapted to illuminate stairs, steps, staircases, pathways, ceiling illumination and the implementation of other architectural concepts

General information

Materials	Powder painted aluminum cast. Lens - safety glass, satin. Silicone gasket. EPDM cable gland.
Mounting method	Mounting of the luminaire: embedded in the wall - hole 215x215x115, mounting in a layered wall - opening 200x200x95 According to the attached assembly instructions
Terminal	Connection terminals: max 5x2,5mm ² Possibility of connecting the luminaire in loops, max 5x1,5mm ² Round insulated cable with a diameter of \varnothing 7...10,5mm
Type of light source	LED module, power supply Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.
Light control	Light control - DALI system
Net / gross weight of luminaire	2,06kg / 2,3kg
Box dimensions [cm]	22,5x23x15

Technical data

LED module	Philips Fortimo SLM C 1203 L09 1619 G7 4K (☞ Datasheet)
Driver	Osram OTi DALI 20/220...240/500 NFC S (☞ Datasheet)
Light source wattage	9,2W
Luminaire wattage	10,7W
Lamp luminous flux	1468lm
Light source efficiency	159,6lm/W
Color temperature	4000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>50 000h
Power Factor luminaire	PF 0,95
THD factor	10%
Ta Rated temperature	+25°C
Max ambient temperature	+40°C

This product contains light source of energy efficiency class **B** / **EPREL**

Optionally, the luminaire is also available:

- For the LED color 2700K [1/1]
- For a different value of the luminous flux
- For a different color of the fitting (according to the RAL color palette)

Terms of sale and other information, after contact with the Sales Department of Norlys

Inrush current	20A / 200 μ s
----------------	-------------------

Spare parts

ZS6031zx0009	Service set.
--------------	--------------

Files to download

BIM Revit	BIM ArchiCAD
-----------	--------------

Indexes

Index	Color	RAL
6031AL	ALUMINIUM	9006
6031GR	GRAPHITE	7016