



Type of luminaire	
Type of luminaire	Wall luminaire.
Photometric body	Diffused, uncovered light.
Characteristics of the luminaire	Modern design plafon type luminaire.

General information	
Materials	Base - powder painted aluminum cast. Front - stainless steel , hot dip galvanized steel, powder coated steel. Lens - safety glass, satin. Silicone gasket.
Mounting method	Fixing of the luminaire: 2 holes $\varnothing$ 4,5mm, spacing 170x50mm.
Terminal	Connection terminals: max 3x2,5mm <sup>2</sup> , possibility to connect luminaire in loop max 3x1,5mm <sup>2</sup> . A round wire in the isolation with a diameter of $\varnothing$ 7...10,5mm.
Type of light source	LED module, power supply
Light control	Trailing edge dimming
Net / gross weight of luminaire	2,95kg / 3,7kg
Box dimensions [cm]	27x26x27

Technical data	
LED module	Philips Strip 0.5ft 550lm 830 FC HV4
Light source wattage	4W
Luminaire wattage	5,2W
Lamp luminous flux	648lm
Light source efficiency	162lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>70 000h
Power Factor luminaire	PF 0,9
Ta Rated temperature	+25°C
Max ambient temperature	+25°C

This product contains light source of energy efficiency class **A++**

Inrush current	1A/15,2 $\mu$ s
----------------	-----------------

Maximum number of luminaires of this type per MCB:  
**B 10A:** 157, **B 16A:** 250, **C 10A:** 260, **C 16A:** 425

Spare parts	
06650004	Lens.
08652663	Gasket.
46999609	LED module.
46999746	Power supply.

**Files to download**  
 Manual

Indexes		
Index	Color	RAL
655B	BLACK	9005
655CO	COPPER	-
655GA	GALVANIZED	-
655ST	STAINLESS STEEL	-