

270



Ø115

C€ [A[

| | characteristics of the furniture | install on corners of architectural | |
|------------------------------------|---|--|--|
| | General information | | |
| | Materials | Hot-dip galvanized steel. Powder stabilized. EPDM cable gland. | |
| | Mounting method | Fixing the luminaire: using the atta | |
| | Terminal | Connection terminals: max 2x2,5r max 2x1,5mm². A round wire in th | |
| | Type of light source | E27 lamp | |
| | Net / gross weight of luminaire | 2,2kg / 3kg | |
| | Box dimensions [cm] | 32,3x32,3x36 | |
| ↓ ↓ ↓ ↓ ↓ ↓ | Technical data | | |
| | E27 lamp | QA55 / LED A5560 | |
| | Light source wattage | MAX 57W / LED 9W | |
| | Ta Rated temperature | +25°C | |
| | This product contains light source of energy efficiency class A+ > D | | |
| | Possibility to order the luminaire with LED E27 lamp Philips Master LED | | |
| | Accessories sold separately | | |
| 320 | 1.50%%0000 | NA | |

IP

55

E27

220-240V 50-60Hz

| ACCESSORES sold separately | |
|----------------------------|-----------------------------|
| 153XX0009 | Mounting corner |
| 159XX0009 | Luminaire mounting distance |
| 46999021 | LED E27 lamp |

| Osram ECO PRO Classic 57<=>75W E27 | Philips ECO Classic 53<=>75W E27 |
|---|--|
| Osram LED Parathom Classic / Retrofit E27 | Philips Master LEDbulb / Classic / CorePro E27 |

| Indexes | | | |
|---------|------------|------|--|
| Index | Color | RAL | |
| 690B | BLACK | 9005 | |
| 690GA | GALVANIZED | - | |

Norlys AS P.B 1014 Hoff, 0218 Oslo Hovfaret 4B, 0275 Oslo Norway +47 24 12 40 11 firmapost@norlys.no







Завантажено з mamadecor.ua

Larvik 690XX0009 23.07.2021 v.09.2 www.norlys.com

| Type of luminaire | | |
|----------------------------------|--|--|
| Type of lumianire | Wall luminaire. | |
| Photometric body | Uncovered light. | |
| Characteristics of the luminaire | Wall-mounted luminaire in Scandinavian design, for general use. Possibility to install on corners of architectural objects. IP of lighting chamber - 55. | |
| General information | | |
| Materials | Hot-dip galvanized steel. Powder painted steel. Lens - clear polycarbonate, UV stabilized. EPDM cable gland. | |
| Mounting method | Fixing the luminaire: using the attached mounting box. | |
| Terminal | Connection terminals: max 2x2,5mm². Possibility to connect luminaire in loop max 2x1,5mm². A round wire in the isolation with a diameter of ø610mm. | |
| Type of light source | E27 lamp | |
| Net / gross weight of luminaire | 2,2kg / 3kg | |
| Box dimensions [cm] | 32,3x32,3x36 | |
| Technical data | | |
| E27 lamp | QA55 / LED A5560 | |
| Light source wattage | MAX 57W / LED 9W | |
| Ta Rated temperature | +25°C | |

Dbulb 806lm / 8,5W / 2700K (dimmable).

| Recommended li | ght sources | |
|-----------------------|----------------------|--------------------|
| Osram ECO PRO Classic | 57<=>75W E27 | Philips ECO Classi |
| Osram LED Parathom Cl | assic / Retrofit E27 | Philips Master LED |
| Spare parts | | |
| 06240003 | Lens. | |
| Files to download | ł | |
| Manual | | |
| Indexes | | |
| Index | Color | |

| Index | Color | RAL |
|-------|------------|------|
| 690B | BLACK | 9005 |
| 690GA | GALVANIZED | - |

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.