



Type of luminaire	
Type of luminaire	Wall luminaire.
Photometric body	Double-sided light with 4° beam angle up and 62° beam angle down.
Characteristics of the luminaire	Luminaire with a wide range of applications for example for illumination of walls and facade surfaces or any other architectural concepts.

General information	
Materials	Powder painted aluminum cast. Lens - safety glass, transparent. Silicone gasket. EPDM cable gland.
Mounting method	Fixing of the luminaire: 2 holes \varnothing 7mm, spacing 100x80mm.
Terminal	Connection terminals: max 3x2,5mm ² , possibility to connect luminaire in loop max 3x1,5mm ² . A round wire in the isolation with a diameter of \varnothing 7...10,5mm.
Type of light source	G12 lamp, electronic ballast
Light control	Non-dimmable luminaire
Net / gross weight of luminaire	4,21kg / 4,69kg
Box dimensions [cm]	20x17x28

Technical data	
HIT-CE lamp	HIT-CE
Light source wattage	70W
Lamp luminous flux	~ 7800lm
Light source efficiency	111,4lm/W
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class **A+**

Recommended light sources	
Philips Master Colour CDM-T 70W G12	Osram Powerball HCI-T 70W G12

Spare parts	
46100003	Electronic ballast.

Files to download	
Manual	BIM Revit
BIM ArchiCAD	

Indexes		
Index	Color	RAL
780AL	ALUMINIUM	9006
780GR	GRAPHITE	7016