



## Type of luminaire

Type of luminaire	Ceiling luminaire.
Photometric body	Single-sided, symmetric light facing down.
Characteristics of the luminaire	Classic design ceiling luminaire. For lighting private areas and public spaces.

## General information

Materials	Powder painted aluminum cast. Lens - safety glass, satin. Silicone gasket. EPDM cable gland.
Mounting method	Fixing of the luminaire: 2 holes $\varnothing 4,5\text{mm}$ , spacing 68x68mm.
Terminal	Connection terminals: max 3x2,5mm <sup>2</sup> , possibility to connect luminaire in loop max 3x1,5mm <sup>2</sup> . A round wire in the isolation with a diameter of $\varnothing 7 \dots 10,5\text{mm}$ .
Type of light source	LED Gu10 lamp, 25D
Light control	Phase-dimming (TRIAC).
Net weight of luminaire	0,65kg
Box dimensions [cm]	12x8,5x13,5

## Technical data

LED GU10 lamp	Master LED ExpertColor 25D 3,9W $\leftrightarrow$ 35W PAR16 Gu10
Light source wattage	3,9W
Luminaire wattage	3,9W
Lamp luminous flux	$\sim 265\text{lm}$
Luminaire luminous flux	210lm
Light source efficiency	67,9lm/W
Efficiency of the luminaire	53,8lm/W
Color temperature	2700K
Colour rendering index CRI	90
Rated life time L70/B50 at 25°C	40 000h
Power Factor luminaire	PF >0,8
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class **A+**

## Recommended light sources

Osram LED Parathom Advanced / Pro max 4W PAR16 Gu10 Philips Master LED max 4W PAR16 Gu10

## Spare parts

06790005	Lens.
46102507	LED Gu10 lamp.

## Files to download

Photometric LDT files	Photometric IES files
3D models and drawings	Manual

## Indexes

Index	Color	RAL
796AL	ALUMINIUM	9006
796B	BLACK	9005
796GR	GRAPHITE	7016
796W	WHITE	9003