


BULB LED G9, 7W

ceramic housing, plastic PC

9197 3000K 10933 4000K

BULB LED G9, 7W 9197




REFLECTOR LED, GU10, R35, 4W

plastic

10230 3000K 10231 4000K

REFLECTOR LED, GU10, R35, 4W 10230




BULB LED G9, 4W

plastic PC

7503 3000K 7504 4000K

BULB LED G9, 4W 7504




REFLECTOR LED, GU10, R50, 7W

plastic

9180 3000K 9178 4000K
8348 3000K 8347 4000K

REFLECTOR LED, GU10, R50, 7W 8347



BULB LENS LED, G9, 3W

ceramic housing, plastic PC

9173 3000K 8447 4000K

BULB LENS LED, G9, 3W 9173

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Power factor	Lifetime
9197	7W LED	3000K	750 lm	360°	≥ 80	~220-230 V, 50/60 Hz	>0.5	25000h
10933	7W LED	4000K	900 lm	360°	≥ 80	~220-230 V, 50/60 Hz	>0.5	25000h
7503	4W LED	3000K	380 lm	360°	≥ 80	~220-230 V, 50/60 Hz	>0.5	25000h
7504	4W LED	4000K	390 lm	360°	≥ 80	~220-230 V, 50/60 Hz	>0.5	25000h
9173	3W LED	3000K	330 lm	90°	≥ 80	~220-230 V, 50/60 Hz	>0.5	25000h
8447	3W LED	4000K	310 lm	90°	>80	~220-230 V, 50/60 Hz	>0.5	25000h

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Power factor	Lifetime
9180	7W LED	3000K	600 lm	50°	≥ 80	~220-230 V, 50/60 Hz	>0.7	25000h
9178	7W LED	4000K	600 lm	50°	≥ 80	~220-230 V, 50/60 Hz	>0.7	25000h
8348	7W LED	3000K	600 lm	50°	≥ 80	~220-230 V, 50/60 Hz	>0.7	25000h
8347	7W LED	4000K	600 lm	50°	≥ 80	~220-230 V, 50/60 Hz	>0.7	25000h
10230	4W LED	3000K	370 lm	70°	>80	~220-230 V, 50/60 Hz	>0.5	20000h
10231	4W LED	4000K	400 lm	70°	>80	~220-230 V, 50/60 Hz	>0.5	20000h

WHITE

WHITE BLACK