
LUMINAIRE PHOTOMETRIC TEST REPORT

8727 CL IOS LED BLACK 30W, 4000K, ANGLE36°



Description Lines

| | |
|-------------------|---|
| Manufacturer: | NOWODVORSKI LIGHTING |
| Model name: | 8727,CL IOS LED BLACK 30W,4000K,ANGLE36 |
| File name: | 8727,CL IOS LED BLACK 30W,4000K,ANGLE36.ltd |
| Date: | 2019-11-26 |
| Report number: | EF 19/12/2019/49; EF 19/12/2019/50 |
| Diameter: | 135mm |
| Height: | 135mm |
| IP rating: | IP 20 |
| Protection class: | I |
| Dimmable: | No |

Equipment

| | |
|-----------------------|---------------------------------------|
| Test system: | EVERFINE GO-2000B_V1 SYSTEM V2.00.417 |
| Temperature: | 25 +/-1 °C |
| Humidity: | 65.0% |
| γ interval: | 1 deg |
| C interval: | 10 deg |
| γ range: | 0-90 deg |
| Measurement distance: | 6.56 m |

Nowodvorski sp. j.

ul. Bojemskiego 11, 42-202 Częstochowa, POLSKA, NIP: PL 5731015208


Tel. +48 34 344 91 10, 344 91 11, fax +48 34 344 91 12

www.nowodvorski.com

Photometric data

| | |
|-----------------------------|------------|
| Total luminous flux: | 2802.42 lm |
| Color temperature: | 4012 K |
| x: | 0.3828 |
| y: | 0.3872 |
| Color rendering index: | 90.1 |
| Wattage: | 28.445 W |
| U | 230.61 V |
| I | 0.1276 A |
| Power factor: | 0.9670 |
| Luminous efficacy: | 98.52 lm/W |
| Flux in lower hemisphere: | 100.0% |
| Flux in upper hemisphere: | 0.0% |
| Maximum luminous intensity: | 8371 cd |
| Light output ratio (LOR): | 100.00% |

Beam cone diagram Beam angle 36°




Nowodvorski sp. j.

ul. Bojemskiego 11, 42-202 Częstochowa, POLSKA, NIP: PL 5731015208

Tel. +48 34 344 91 10, 344 91 11, fax +48 34 344 91 12


www.nowodvorski.com

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Luminous intensity [cd]
 C0-C180 —
 C90-C270 —

Spectral distribution



Nowodvorski sp. j.
 ul. Bojemskiego 11, 42-202 Częstochowa, POLSKA, NIP: PL 5731015208
 Tel. +48 34 344 91 10, 344 91 11, fax +48 34 344 91 12
www.nowodvorski.com