

02 Recessed Spots Fixed LED>The Round Mirror Range

10106X/B/W



6W Recessed spot, IP20.

Complete with 150mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

| | |
|----------------------|-----------------------------|
| Item Group | 02 Recessed Spots Fixed LED |
| Family | The Round Mirror Range |
| Order Code | 10106X/B/W |
| Colour | Black |
| Material | Aluminium |
| Shape | Circular |
| Height | 48mm |
| Diameter | 89mm |
| Cutout Hole Diameter | 75mm |
| Recessed Ceiling | Yes |
| Depth Required | 60mm |
| Indoor | Yes |

Electrical Characteristics

Gear

Built In

Fitting + Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

6W

IP Rating

IP20

Light Source

LED built in

Dimmable

No

Fitting

Input Type

Constant Current

Input Current

150mA

Voltage

36V

Safety Class



Power(Watts)

5,4W

IP Rating

IP20

Light Source

LED built in

LED Type

SMD 3030

LED Brand

Sanan

LED Number

6

F Mark




Gear

Gear Type

Led Driver

Input Voltage

220-240V

| | |
|------------------|---|
| 50 Hz | Yes |
| 60 Hz | Yes |
| Power(Watts) | 4,2-6,3W |
| Power Factor | 0,5 |
| Constant Current | Yes |
| 150mA | 28-42V |
| IP Rating | IP20 |
| Safety Class |  |
| Dimmable | No |
| Ambient Temp | -20°C...+60°C |
| Operating Temp | 85°C |
| Brand | Eaglerise |
| Protection | Over Load Protection, Over Voltage Protection, Short circuit Protection |

Illumination Data

| | |
|----------------------|---|
| Colour Temperature | 3000K |
| Lumen Output | 480lm |
| Light Efficiency | 80lm/W |
| CRI | 90 |
| Beam Angle | 38° |
| Illumination Diagram |  |
| Dark Light | Yes |

Packing Info

| | |
|------------|---------------|
| Pcs/Carton | 40 |
| Barcode | 5291889074588 |
| HS Code | 9405413990 |

Certification & Warranty

switch to
one light!

one
LIGHT

