

06 Downlights Fixed LED>Floating Panels Range Adjustable Cut Out Hole

10114CE/W

14W Downlight LED, IP20

Complete with 300mA driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery



Physical Specification

Item Group

06 Downlights Fixed LED

Family

Floating Panels Range Adjustable Cut Out Hole

Order Code

10114CE/W

Colour

White

Material

Aluminium

Diffuser Material



PC


Shape

Circular

| | |
|----------------------|------------|
| Height | 24mm |
| Diameter | 160mm |
| Cutout Hole Diameter | 60mm-140mm |
| Recessed Ceiling | Yes |
| Depth Required | 40mm |
| Indoor | Yes |
| Adjustable | No |

Electrical Characteristics

| | |
|------------------|---|
| Gear | External-Included |
| Fitting + Driver | |
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Safety Class |  |
| Power(Watts) | 14W |
| IP Rating | IP20 |
| Light Source | LED built in |
| Dimmable | No |
| F Mark |  |

| | |
|---------------|---|
| Fitting | |
| Input Type | Constant Current |
| Input Current | 300mA |
| Voltage | 40V |
| Safety Class |  |
| Power(Watts) | 12W |
| IP Rating | IP20 |
| Light Source | LED built in |
| LED Type | SMD 4014 |

Gear

Gear Type

Led Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Power(Watts)

9-14W

Power Factor

0,5

Constant Current

Yes

300mA

30-42V

IP Rating

IP20

Safety Class



Dimmable

No

Housing Material

Plastic

Output Terminal

Cable

Brand

Eaglerise

Illumination Data

Colour Temperature

3000K

Lumen Output

1550lm

Light Efficiency

110,71lm/W

CRI

80

Illumination Diagram



Packing Info

Pcs/Carton

40

Barcode

5291889066439

HS Code

9405409900

Certification & Warranty

Warranty

2 Years

Weee Directive

Yes

switch to
one light!

one
LIGHT

