

06 Downlights Fixed LED&gt;The SMD Dark Light Range

10122D/W/C



22W Dark Light LED Downlight .

Supplied with 500mA non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



## Downloads



## Dimensions



## Physical Specification

|                      |                          |
|----------------------|--------------------------|
| Item Group           | 06 Downlights Fixed LED  |
| Family               | The SMD Dark Light Range |
| Order Code           | 10122D/W/C               |
| Colour               | White                    |
| Material             | Die Cast                 |
| Shape                | Circular                 |
| Height               | 55mm                     |
| Diameter             | 175mm                    |
| Cutout Hole Diameter | 165mm                    |
| Recessed Ceiling     | Yes                      |
| Depth Required       | 75mm                     |
| Indoor               | Yes                      |

## Electrical Characteristics

## Gear

## External-Included

## Fitting + Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

22W

IP Rating

IP20

Light Source

LED built in

Dimmable

No

F Mark



## Fitting

Input Type

Constant Current

Input Current

500mA

Voltage

40V

Safety Class



Power(Watts)

20W

IP Rating

IP20

Light Source

LED built in

LED Type

SMD 2835

LED Brand

Sanan

## Gear

Gear Type

Led Driver

Input Voltage


220-240V

50 Hz

Yes

|                  |   |
|------------------|---|
| 60 Hz            | Yes   |
| Power(Watts)     | 12,5-20W  |
| Power Factor     | 0,9   |
| Constant Current | Yes   |
| 500mA            | 25-40V  |
| IP Rating        | IP20  |
| Safety Class     |  |
| Dimmable         | No  |
| Ambient Temp     | -30? ~ +50?   |
| Housing Material | Plastic   |
| Brand            | Lifud   |

#### Illumination Data

|                      |   |
|----------------------|---|
| Colour Temperature   | 4000K   |
| Lumen Output         | 1870lm  |
| Light Efficiency     | 85lm/W  |
| CRI                  | 80  |
| Beam Angle           | 100°  |
| Illumination Diagram |  |
| Dark Light           | Yes   |

#### Packing Info

|            |               |
|------------|---------------|
| Box Length | 20cm          |
| Box Width  | 7cm           |
| Box Height | 18cm          |
| Pcs/Carton | 20            |
| Barcode    | 5291889060741 |
| HS Code    | 9405409900    |

Certification & Warranty

Warranty

2 Years

Weee Directive

Yes

switch to  
**one light!**

one  
LIGHT

