

06 Downlights Fixed LED&gt;Architectural Downlights Die cast

10128/G/D



28W LED architectural downlight, IP20.

Complete with LED driver.

Complies with standard EN60598-1 and any other specific standards.




## Downloads



## Dimensions



## Gallery



## Physical Specification

Item Group

06 Downlights Fixed LED

Family

Architectural Downlights Die cast

Order Code

10128/G/D

Colour

Grey

Material

Die Cast

Diffuser Material

Acrylic

Shape

Circular

Height	85mm
Diameter	195mm
Cutout Hole Diameter	169mm
Recessed Ceiling	Yes
Depth Required	110mm
Indoor	Yes
Adjustable	No

## Electrical Characteristics

Gear	Built In
------	----------

## Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	28W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

## Fitting

Input Type	Constant Current
IP Rating	IP20
Light Source	LED built in

## Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes

60 Hz
IP Rating
Safety Class
Dimmable
Housing Material
Brand

Yes

IP20



No

Plastic

One Light

## Illumination Data

Colour Temperature
Lumen Output
Light Efficiency
CRI
Beam Angle
Illumination Diagram

6000K

1400lm

50lm/W

80

90°



## Packing Info

Box Length
Box Width
Box Height
Pcs/Carton
Barcode
HS Code

25cm

21,5cm

11,5cm

10

5291889027386

9405409900

## Certification &amp; Warranty

Warranty

2 Years

[Завантажено з mamadecor.ua](http://mamadecor.ua)

Weee Directive

Yes

switch to  
**one light!**

one  
LIGHT

