

06 Downlights Fixed LED>Architectural Downlights Die cast

10128/G/W



28W LED architectural downlight, IP20.

Complete with LED driver.

Complies with standard EN60598-1 and any other specific standards.




Downloads



Dimensions



Gallery



Physical Specification

Item Group

06 Downlights Fixed LED

Family

Architectural Downlights Die cast

Order Code

10128/G/W

Colour

Grey

Material

Die Cast

Diffuser Material

Acrylic

Shape

Circular

Height	85mm
Diameter	195mm
Cutout Hole Diameter	169mm
Recessed Ceiling	Yes
Depth Required	110mm
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	Built In
------	----------

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	28W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting

Input Type	Constant Current
IP Rating	IP20
Light Source	LED built in

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes

60 Hz
IP Rating
Safety Class
Dimmable
Housing Material
Brand

Yes

IP20



No

Plastic

One Light

Illumination Data

Colour Temperature
Lumen Output
Light Efficiency
CRI
Beam Angle
Illumination Diagram

3000K

1150lm

41lm/W

80

90°



Packing Info

Box Length
Box Width
Box Height
Pcs/Carton
Barcode
HS Code

25cm

21,5cm

11,5cm

10

5291889027393

9405409900

Certification & Warranty

Warranty

2 Years

[Завантажено з mamadecor.ua](http://mamadecor.ua)

Weee Directive

Yes

switch to
one light!

one
LIGHT

