

06 Downlights Fixed LED>The Frameless IP65 Range Die cast + PC

10130CF/C



30W LED frameless downlight, IP65. Suitable for Indoor/Outdoor installation and bathroom.

Complete with 700mA driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery



Related items



050148/B



050148/W

Physical Specification

Item Group

06 Downlights Fixed LED

Family

The Frameless IP65 Range Die cast + PC

Order Code

10130CF/C

Завантажено з mamadecor.ua

Colour

White

Material

Die Cast

Diffuser Material

PC

Shape

Circular

Height

22mm

Diameter

215mm

Cutout Hole Diameter

195mm

Recessed Ceiling

Yes

Depth Required

50mm

Indoor

Yes

Outdoor

Yes

Adjustable

No

IK Rating

8

Electrical Characteristics

Gear

External-Included

Fitting + Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

30W

IP Rating

IP65

Light Source

LED built in

Dimmable

No

F Mark



Fitting

Input Type

Constant Current

Input Current	700mA
Voltage	36V
Safety Class	
Power(Watts)	25,2W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD 4014
LED Brand	Zhaochi
F Mark	

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	21-28W
Power Factor	0,9
Constant Current	Yes
700mA	30-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	KEGU

Illumination Data

Colour Temperature	4000K
Lumen Output	2400lm
Light Efficiency	80lm/W
CRI	80

Beam Angle

120°

Завантажено з mamadecor.ua

Illumination Diagram



Packing Info

Box Length

28cm

Box Width

25cm

Box Height

3cm

Box Weight

0.770kg

Pcs/Carton

20

Barcode

5291889057130

HS Code

9405413990

Energy Label



Energy Class

F

Energy Consumption

30kWh/1000h

Certification & Warranty

Warranty

2 years

switch to
one light!

one
LIGHT

