

## 04 Recessed Spots Adjustable LED&gt;The 3W Mini Lighter

11103K/B/W



3W LED Dark Light Recessed adjustable spot, IP20.

Requires 350mA driver.

Complies with standard EN60598-1 and any other specific standards.



## Downloads




## Dimensions



## Must be ordered separately



89004



89004T

## Physical Specification

Item Group

04 Recessed Spots Adjustable LED

Family

The 3W Mini Lighter

Order Code

11103K/B/W

Colour

Black

Material

Aluminium



Shape

Circular

Height	52mm
Diameter	52mm
Cutout Hole Diameter	42mm
Recessed Ceiling	Yes
Depth Required	60mm
Indoor	Yes
Adjustable	1 Direction

## Electrical Characteristics

## Fitting

Input Type	Constant Current
Input Current	350mA
Voltage	8,4V
Safety Class	
Power(Watts)	3W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Bridgelux
LED Number	1
Cable Length	40cm
F Mark	

## Illumination Data

Colour Temperature	3000K
Lumen Output	240lm
Light Efficiency	80lm/W
CRI	90
Beam Angle	30°



Dark Light

Yes

## Packing Info

Box Length

5,5cm

Box Width

5,5cm

Box Height

5,6cm

Pcs/Carton

100

Barcode

5291889070030

HS Code

9405409900

## Certification &amp; Warranty

Warranty

5 Years

Weee Directive

Yes

switch to  
**one light!**

one  
LIGHT

