

04 Recessed Spots Adjustable LED>The COB Adjustable Spots

11106A/AL/W



COB LED recessed spot. Very elegant design with unique design of the reflector. Ideal for replacing halogen spots.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	04 Recessed Spots Adjustable LED
Family	The COB Adjustable Spots
Order Code	11106A/AL/W
Colour	Aluminium
Material	Aluminium
Shape	Circular
Height	61mm
Diameter	92mm
Cutout Hole Diameter	80mm
Recessed Ceiling	Yes
Depth Required	80mm
Indoor	Yes

Electrical Characteristics

Gear

External-Included

Fitting + Driver

Input Voltage

100-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

6W

IP Rating

IP20

Light Source

LED built in

Dimmable

No

F Mark



Fitting

Input Type

Constant Current

Input Current

500mA

Voltage

12V

Safety Class



Power(Watts)

6W

IP Rating

IP20

Light Source

LED built in

LED Brand

Citizen

LED Number

1

F Mark




Gear

Gear Type

Led Driver

Input Voltage

100-240V

50 Hz	Yes
60 Hz	Yes
Power(Watts)	6-9W
Power Factor	0,9
Constant Current	Yes
500mA	12-18
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	-20~50°C
Housing Material	Plastic
Output Terminal	Cable
Brand	HEP

Illumination Data

Colour Temperature	3000K
Lumen Output	475lm
Light Efficiency	79,16lm/W
CRI	80
Beam Angle	36°
Illumination Diagram	

Packing Info

Box Length	11,5cm
Box Width	9cm
Box Height	11,5cm
Pcs/Carton	20
Barcode	5291889033257
HS Code	9405409900

Certification & Warranty

Warranty

2 Years

Weee Directive

Yes

switch to
one light!

one
LIGHT

